



GENERAL NOTES:

- 1 FALL THROUGH TABLET FEEDER FROM INLET INVERT TO OUTLET INVERT IS ONE INCH ±3/8".
- 2 FINISHED GRADE MUST BE MAINTAINED AT LEAST SIX INCHES BELOW TOP OF LID.
- 3 FEEDER BASE HEIGHT MAY BE REDUCED IN SIX INCH INCREMENTS. COVER MUST BE DRILLED TO ALLOW TUBES TO EXTEND THROUGH LID WHEN REDUCING FEEDER HEIGHT.
- 4 WHERE TABLET FEEDER IS INSTALLED WITHOUT MOUNTING BRACKETS, INSTALL ON FOUR INCH SAND OR FINE GRAVEL LEVELING PAD.

PROJECT ENGINEER'S APPROVAL:

I (WE) HEREBY CERTIFY THAT THIS DRAWING HAS BEEN CHECKED AND IS APPROVED FOR USE IN CONFORMITY WITH THE CONTRACT DOCUMENTS.

DATE: _____

NAME: _____

CONTRACTOR'S CERTIFICATION:

I (WE) HEREBY CERTIFY THAT THIS DRAWING HAS BEEN CHECKED AND IS APPROVED FOR USE IN CONFORMITY WITH THE CONTRACT DOCUMENTS.

DATE: _____

NAME: _____

CRITICAL DIMENSIONS

A	0'-10 1/2"	D	0'-0 1/2"
B	2'-0"	E	0'-8"
C	2'-1 1/2"	F	0'-3 1/2"
D	0'-5"	G	0'-10"
E	0'-5 1/4"	H	1'-8"
F	0'-1 3/4" (TYP)	I	0'-11"
G	0'-2" (TYP)	J	0'-6" (TYP)
H	0'-4 1/2" (TYP)	K	
I	0'-1 1/2"	L	

TOLERANCES

NOMINAL DIMENSIONS ARE SHOWN AND MAY VARY ±3/8" FOR ROTOMOLDED COMPONENTS.

U.S. AND FOREIGN PATENTS PENDING	11-14-07	B
norweco	APPROVED BY	BDS
PROMAG ENVIRO	DATE	JMM
TABLET FEEDER	10-2-97	NTS
©	THIS DOCUMENT IS THE PROPERTY OF PROMAG ENVIRO. IT IS TO BE USED ONLY FOR THE PROJECT AND NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.	PC-5-9500