

TEST PUMPS, MANOMETER & CLOG-BUSTER



A) Air-Max® Pro HV Test Pump (Part #273908)

- Larger barrel diameter - fewer strokes per inflation
- 100 psi gauge with molded rubber cover



C) Econ-O-Pump™ Test Pump (Part #273888)

- 200 psi high-pressure gauge with protective cover




B) Air Max® Test Pump (Part #273898)

- 160 psi gauge raised from base for protection
- Textured steel base prevents pump from slipping
- Durable, no-kink hose



Manometer (Part #010205)

- Used for testing gas lines and DWV pipe
- Measures water columns from 0" to 16"
- Reads in increments of 1/10"
- Product Weight: 0.5 lb (.23 kg)



CLOG-BUSTER DRAIN FLUSHER



PART NUMBER	PRODUCT DESCRIPTION
303127	1" – 2" Clog-Buster drain flusher
303135	1.5" – 3" Clog-Buster drain flusher
303143	4" – 6" Clog-Buster drain flusher
006193	Faucet adapter

Clog-Buster Drain Flusher Features:

- Unclogs drain pipes in seconds
- Simply remove aerator from faucet and attach faucet adapter
- Attaches to standard garden hose fitting
- Insert clog buster as far as possible into drain and slowly turn on the cold water - clog should dislodge almost immediately
- Eliminates need for using chemicals



POINT REPAIR CARRIER




Cherne's point repair carriers are well-suited for most point repair systems. Available for multi-size line covers pipe sizes from 4"–36" diameters and lengths up to 15'. Cherne's carriers are known for both their durability and reliability. Custom lengths are available upon request.

Features:

- Maximum pipe contact guides and center line ensure proper placement of repair medium to minimize waste and increase productivity
- 1/4" NPT Inflation Port with male quick disconnect for ease of connection
- Durable, flexible natural corded rubber
- Bypass design allows sewage bypass during repair – no need to shut down the line
- The flexible design allows all units to be folded in half for transport
- Redesigned integrated caster wheel assembly and bypass channel have been optimized for ease of movement and enhanced bypass of effluent
- Reduced deflated diameters

POINT REPAIR CARRIERS



Point Repair Carrier

PART NUMBER	FOR PIPE SIZE / DIAMETER	LENGTH	INFLATION PRESSURE	BYPASS DIAMETER	WEIGHT (LBS.)	DEFLATED DIAMETER			CONTACT LENGTH	
						PLUG DIAMETER	INSIDE WHEEL	OUTSIDE WHEEL	MAXIMUM	MINIMUM
279058	4"-6" (100-150 mm)	5' (1.5 m)	45 psi	NA	10	2.65"	NA	NA	53"	47"
279108	4"-6" (100-150 mm)	10' (3 m)	45 psi	NA	13.5	2.65"	NA	NA	113"	107"
279158	4"-6" (100-150 mm)	15' (4.5 m)	45 psi	NA	17.5	2.65"	NA	NA	173"	167"
287058	8"-12" (200-300 mm)	5' (1.5 m)	25 psi	2"	22	4.75"	5.14"	5.6"	48"	42"
287108	8"-12" (200-300 mm)	10' (3 m)	25 psi	2"	30	4.75"	5.14"	5.6"	108"	102"
287158	8"-12" (200-300 mm)	15' (4.5 m)	25 psi	2"	37.5	4.75"	5.14"	5.6"	168"	162"
288058	12"-16" (300-400 mm)	5' (1.5 m)	15 psi	2"	25	8.56"	10"	11.9"	50"	45"
288108	12"-16" (300-400 mm)	10' (3 m)	15 psi	2"	35	8.56"	10"	11.9"	110"	105"
288158	12"-16" (300-400 mm)	15' (4.5 m)	15 psi	2"	45	8.56"	10"	11.9"	170"	165"
289058	18"-24" (450-600 mm)	5' (1.5 m)	15 psi	2"	74	14.68"	15.42"	17.9"	49"	43"
289108	18"-24" (450-600 mm)	10' (3 m)	15 psi	2"	84	14.68"	15.42"	17.9"	109"	103"
289158	18"-24" (450-600 mm)	15' (4.5 m)	15 psi	2"	94	14.68"	15.42"	17.9"	169"	163"
284058	24"-36" (600-914 mm)	5' (1.5 m)	15 psi	4"	107	19.05"	19.56"	22.3"	48"	33"
284108	24"-36" (600-914 mm)	10' (3 m)	15 psi	4"	140.5	19.05"	19.56"	22.3"	108"	93"
284158	24"-36" (600-914 mm)	15' (4.5 m)	15 psi	4"	182	19.05"	19.56"	22.3"	168"	153"

POINT REPAIR CARRIER CAGES



PART NUMBER	DESCRIPTION
287008	8-12 Carrier Cage (set of 2)
288008	12-16 Carrier Cage (set of 2)
289008	18-24 Carrier Cage (set of 2)
284008	24-36 Carrier Cage (set of 2)

EXTENSION HOSES & TUB PLUGS



Tub Waste & Overflow Plugs: (Part #012678)

- Isolate bath waste for air/water testing
- Yellow ABS plastic
- Natural rubber gasket
- Threads into drain spuds with center hole and center hole overflow elbows
- Can only be used in overflow drains with 1/2" and 3/8" center hole diameters

Extension/Inflation/Read Back Hoses with Gauge

- Well suited for plugs up to 15"
- 0–100 psig gauge
- 3/16" ID hose

Extension/Inflation Hoses

- Well suited for plugs up to 15"
- 3/16" ID hose

EXTENSION/INFLATION/READ BACK HOSES WITH GAUGE



PART NUMBER	DESCRIPTION
274218	5' Extension hose with gauge
274228	10' Extension hose with gauge
274238	20' Extension hose with gauge
274248	30' Extension hose with gauge
274268	50' Extension hose with gauge
274298	100' Extension hose with gauge

EXTENSION/INFLATION HOSES



PART NUMBER	DESCRIPTION
274011	2' Extension hose
274038	3' Extension hose
274054	5' Extension hose
274100	10' Extension hose
274208	20' Extension hose
055816	Deflator with clamp (female replacement end)
055808	Inflator with clamp (male replacement end)
277048	Replacement O-rings, 10 Pack

TEST GAUGES & CHAIN ASSEMBLIES



Test Gauges (without Test Body):

- 2" metal face
- High-quality brass 1/4" connection

Test Gauges (with Hexagonal Test Body):

- 2" metal face
- Chrome plated body
- 1/8" Schrader valve
- 3/4" NPT(F) pipe connection

Replacement Ring & Chain Assembly:

- Prevents Test-Ball® plugs from falling down a line
- Includes safety tag

TEST GAUGES WITHOUT TEST BODY



PART NUMBER	DESCRIPTION	
000698	0–15 psi pressure range	.1 psi increments
000628	0–30 psi pressure range	.5 psi increments
000638	0–60 psi pressure range	1 psi increments
000648	0–100 psi pressure range	2 psi increments

TEST GAUGES WITH TEST BODY



PART NUMBER	DESCRIPTION	
024568	0–15 psi pressure range	.1 psi increments
019698	0–30 psi pressure range	.5 psi increments
019708	0–60 psi pressure range	1 psi increments
019718	0–100 psi pressure range	2 psi increments

REPLACEMENT RING & CHAIN ASSEMBLIES



PART NUMBER	PRODUCT DESCRIPTION
059708	2" Ring with 12" chain
059718	3" Ring with 12" chain
059728	4" Ring with 12" chain
059748	6" Ring with 12" chain
059758	2" Ring with 24" chain
059768	3" Ring with 24" chain
059778	4" Ring with 24" chain
059798	6" Ring with 24" chain

POLY-LIFT LINES

Heavy Duty Poly Lift Line:

- Stainless steel hardware and fittings
- Clear coated zinc plated steel hooks
- Industrial grade heavy duty spiral wrap
- Heavy duty rubber gauge cover
- Retard gauge: helps prevent “peg-out” damage
- 3/8" heavy duty ID hose
- Industrial quick disconnects

Hi-Flow Poly Lift Line:

- *Greater Lifting Strength*
- Recommended for plugs 6" to 48"
- Retard gauge: helps prevent “peg-out” damage
- Heavy duty rubber gauge cover protects gauge
- 3/8" heavy duty ID hose for quick inflate/deflate
- Quick-dump valve for easy deflation
- Industrial quick disconnects
- Designed for use with plugs with removable inflator valve

Poly Lift Line:

- Great for plugs up to 15"
- 3/16" ID hose
- Threaded connection fittings

HEAVY DUTY POLY LIFT LINE



PART NUMBER	PRODUCT LENGTH
395108	HD Poly Lift Line, 10' with industrial quick disconnects and gauge
395208	HD Poly Lift Line, 20' with industrial quick disconnects and gauge
395308	HD Poly Lift Line, 30' with industrial quick disconnects and gauge
395408	HD Poly Lift Line, 40' with industrial quick disconnects and gauge
395508	HD Poly Lift Line, 50' with industrial quick disconnects and gauge

HI-FLOW HOSE



PART NUMBER	PRODUCT LENGTH
383108	Hi-Flow Hose, 10' with gauge
383208	Hi-Flow Hose, 20' with gauge
383308	Hi-Flow Hose, 30' with gauge
383408	Hi-Flow Hose, 40' with gauge
383508	Hi-Flow Hose, 50' with gauge
380108	Hi-Flow Hose, 10' without gauge
380208	Hi-Flow Hose, 20' without gauge
380308	Hi-Flow Hose, 30' without gauge
380408	Hi-Flow Hose, 40' without gauge
380508	Hi-Flow Hose, 50' without gauge

Consult factory for lines without gauges.

POLY-LIFT LINE



PART NUMBER	PRODUCT LENGTH
261076	10'
261084	20'
261106	30'
261114	40'